


This drawing is property of I. Arruti and must not be copied, exhibited or furnished without the written consent of I. Arruti



Notes:

- Both sides of the pad are finished to present excellent electrical contact surfaces
- Electrical connection pads will be supplied with a protective covering
- Hot dip galvanized according to ASTM A153
- Tolerances unless otherwise stated to be up to and including 1.4" ±0.027 Over 1.4" ±2%
- All dimensions in inches

8	4	SPRING LOCK 1/2" ASME B18.21.1	STAINLESS STEEL
7	8	FLAT WASHER 1/2" ASME B18.21.1	STAINLESS STEEL
6	4	HEX NUT 1/2" ASME B18.2.2	STAINLESS STEEL
5	4	BOLT 1/2"x2.5 ASME B18.2.1	STAINLESS STEEL
4	1	EYE TERMINAL	FORGING STEEL GALV.
3	1	JUMPER CONNECTOR DC-47,5	ALUMINIUM ALLOY
2	1	DEAD END LUG	ALUMINIUM
1	1	CLAMP BODY	ALUMINIUM ALLOY
N	QTY	DENOMINATION	MATERIAL

MOD.	DATE	MODIFICATION				DRAWN BY
 INDUSTRIAS ARRUTI S.A.		CODE				
		EYE TERMINAL COMPRESSION CLAMP C-469-AA/AM-IX FOR ACAR 927,2 MCM CONDUCTOR				
UNIT (inch)		Recomended Torque: 35 f+lb				
		Aprox. Weight: 9.76 lb				
		U.S.: 95% of conductor R.B.S.				
DRAWN	J.E.	05-05-21	SCALE	DWG No	ISSUE	
CHECKED	I.L.	05-05-21	D/S	C469AAAMIX	1	

ARCHIVO:usacompression