


This drawing is property of I. Arruti and must not be copied, exhibited or furnished without the written consent of I. Arruti



Notes:

- Both sides of the pad are finished to present excellent electrical contact surfaces
- Electrical connection pads will be supplied with a protective covering
- Hot dip galvanized according to ASTM A153
- Tolerances unless otherwise stated to be up to and including 1.4" ± 0.027 Over 1.4" ± 2%
- All dimensions in inches

QTY	DENOMINATION	MATERIAL
9	1 FILLER PLUG	ALUMINIUM
8	4 SPRING LOCK 1/2" ASME B18.21.1	STAINLESS STEEL
7	8 FLAT WASHER 1/2" ASME B18.21.1	STAINLESS STEEL
6	4 HEX NUT 1/2" ASME B18.2.2	STAINLESS STEEL
5	4 BOLT 1/2"x2.5 ASME B18.2.1	STAINLESS STEEL
4	1 EYE TERMINAL	FORGING STEEL GALV.
3	1 JUMPER CONNECTOR DC-38,5	ALUMINIUM
2	1 DEAD END LUG	ALUMINIUM
1	1 CLAMP BODY	ALUMINIUM

MOD.	DATE	MODIFICATION	DRAWN BY				
 INDUSTRIAS ARRUTI S.A.		CODE					
		EYE TERMINAL COMPRESSION CLAMP C-235-SS/AM-IX FOR ACSS IBIS CONDUCTOR					
 UNIT (inch)		Recomend Torque: 35 ftlb Aprox. Weight: 6.65 lb U.S.: 95% of conductor R.B.S.					
		DRAWN	J.E.	09-09-20	SCALE	DWG No	ISSUE
CHECKED	I.L.	09-09-20	D/S	C235SSAMIX	0		

ARCHIVO: usccompression