


This drawing is property of I. Arruti and must not be copied, exhibited or furnished without the written consent of I. Arruti



Notes:

- Both sides of the pad are finished to present excellent electrical contact surfaces
- Electrical connection pads will be supplied with a protective covering
- Hot dip galvanized according to ASTM A153
- Tolerances unless otherwise stated to be up to and including 1.4" ±0.027 Over 1.4" ±2%
- All dimensions in inches

8	2	SPRING LOCK 1/2" ASME B18.21.1	STAINLESS STEEL
7	4	FLAT WASHER 1/2" ASME B18.21.1	STAINLESS STEEL
6	2	HEX NUT 1/2" ASME B18.2.2	STAINLESS STEEL
5	2	BOLT 1/2"x2.5 ASME B18.2.1	STAINLESS STEEL
4	1	EYE TERMINAL	FORGING STEEL GALV.
3	1	JUMPER CONNECTOR DC-38,5	ALUMINIUM
2	1	DEAD END LUG	ALUMINIUM
1	1	CLAMP BODY	ALUMINIUM
N	QTY	DENOMINATION	MATERIAL

MOD.	DATE	MODIFICATION			DRAWN BY
 INDUSTRIAS ARRUTI S.A.		CODE			
		EYE TERMINAL COMPRESSION CLAMP C-236-AA/AM-IX FOR AAAC CAIRO CONDUCTOR			
F 40513		UNIT (inch)	Recomended Torque: 35 f+lb		
DRAWN			Aprox. Weight: 5.85 lb		
J.E.			U.S.: 95% of conductor R.B.S.		
CHECKED		I.L.	05-05-21	SCALE	DWG No
			05-05-21	D/S	C236AAAMIX
					ISSUE
					1

ARCHIVO:usacompression