


This drawing is property of I. Arruti and must not be copied, exhibited or furnished without the written consent of I. Arruti



Notes:

- Both sides of the pad are finished to present excellent electrical contact surfaces
- Electrical connection pads will be supplied with a protective covering
- Hot dip galvanized according to ASTM A153
- Tolerances unless otherwise stated to be up to and including 1.4" ±0.027 Over 1.4" ±2%
- All dimensions in inches

9	1	FILLER PLUG	ALUMINIUM
8	4	SPRING LOCK 1/2" ASME B18.21.1	STEEL GALVANIZED
7	8	FLAT WASHER 1/2" ASME B18.21.1	STEEL GALVANIZED
6	4	HEX NUT 1/2" ASTM A523	STEEL GALVANIZED
5	4	BOLT 1/2"x2.5 ASTM A325	STEEL GALVANIZED
4	1	EYE TERMINAL 7460-F	FORGING STEEL GALV.
3	1	JUMPER CONNECTOR DC	ALUMINIUM
2	1	DEAD END LUG 508	ALUMINIUM
1	1	CLAMP BODY	ALUMINIUM
N	QTY	DENOMINATION	MATERIAL

MOD.	DATE	MODIFICATION			DRAWN BY
		CODE			
		EYE TERMINAL COMPRESSION CLAMP C-540/AM-IX FOR ACSR CARDINAL CONDUCTOR			
		UNIT (inch)	Recomended Torque: 35 f+lb		
			Aprox. Weight: 13.20 lb		
			U.S.: 95% of conductor R.B.S.		
DRAWN	J.E.	24-01-22	SCALE	DWG No	ISSUE
CHECKED	I.L.	24-01-22	D/S	C540AMIX	0

ARCHIVO: 32aH