This drawing is property of I. Arruti and must not be copied, exhibited or furnished without the written consent of I. Arruti



MARKS
- ⚠ & LOT
- REFERENCE OF THE CLAMP
- CONDUCTOR NAME
- MIN. RECOMMENDED PRESS
- DIE SIZE
- COMPRESSION AREA
- RECOMMENDED TORQUE FOR JUMPER

DIMENSIONS BEFORE COMPR.

ARCHIVO:usacompresion

Notes:

- Both sides of the pad are finished to present excellent electrical contact surfaces
- Electrical connection pads will be supplied with a protective covering
- Hot dip galvanized according to ASTM A153
- Tolerances unless otherwise stated o be up to and incluiding 1.4" mm. ±0.7 mm. Over 1.4" mm. ±2%
- All dimensions in inches

N	QTY	DENOMINATION	MATERIAL
9	1	FILLER PLUG	ALUMINIUM
8	4	SPRING LOCK 1/2" ASME B18.21.1	STAINLESS STEEL
7	8	FLAT WASHER 1/2" ASME B18.21.1	STAINLESS STEEL
6	4	HEX NUT 1/2" ASME B18.2.2	STAINLESS STEEL
5	4	BOLT 1/2"x2.5 ASME B18.2.1	STAINLESS STEEL
4	1	EYE TERMINAL 7470-F	FORGING STEEL GALV.
3	1	JUMPER CONNECTOR DC-66	ALUMINIUM
2	1	DEAD END LUG	ALUMINIUM
1	1	CLAMP BODY	ALUMINIUM

MOD.	DATE	MODIFICATION	DRAWN BY

INDUSTRIAS ARRUTI S.A.

CODE

EYE TERMINAL COMPRESSION CLAMP C-977/AM-IX
FOR ACSR CHUKAR CONDUCTOR

UNIT (inch)

Recomended Torque: 35 ftlb
Aprox. Weight: 19.80 lb
U.S.: 95% of conductor R.B.S.

F40513	NAME				
DRAWN	J.E.	06-07-21	SCALE	DWG No	ISSUE
CHECKED	I.L.	06-07-21	D/S	C977AMIX	0